

# Fireriser® UL FM Gate Valves

- All Gate valves with SS Stems for better corrosion resistance (Competitors use common brass)
- Available in 200 PSI and 300 PSI Pressure Ratings
- Non Rising Stem and Rising Stem (OS&Y) Types available
- Fusion Bonded Epoxy Coated In Fire Engine Red
- No Painting Required Colored Red
- Post Indicators –Both Upright and Wall Types
- Pre-Grooved Stems for tamper switch attachment
- ANSI125-250/BS/EN and BS 10 Table E Flanged ends
- Pressure tested at 5 times working pressure for approval
- Tested for 1000 cycles, open/closed for approval

# OS&Y



# NRS



# PIV



# Fireiser® Butterfly Valves

- Grooved and Wafer Types
- 175PSI and 300 PSI Pressure Ratings
- Internal monitor switches as standard
- Nylon Coated Bodies –Grooved End Type
- Metric and ANSI size Grooved end connections
- Size range from 2 ½" (65mm) to 12"(300mm)
- UL Listed/FM Approved
- Tested at 5 times working pressure for approval
- Tested for 1000 cycles, open/closed for approval

# Grooved



# Wafer



# Firefly® Butterfly Valves

- From 1" (25mm) to 2 1/2" (65mm)
- UL Listed FM approved
- 1" (25mm) to 2 1/2" (65mm) Threaded Ends
- 2" (50mm) and 2 1/2" (65mm) Grooved ends
- Internal monitor switches as standard
- Metric and ANSI Grooved Ends Available
- Ideal as Zone shut off Valves.
- Cost less than gate valves
- Easier to install than cumbersome and expensive gate valves.
- Tested at 5 times working pressure for approval
- Tested for 1000 cycles, open/closed for approval



# Firefly

