



## VENF.EX26542 Flexible Sprinkler Hose with Fittings

Page Bottom

### Flexible Sprinkler Hose with Fittings

See General Information for Flexible Sprinkler Hose with Fittings

**ZHEJIANG TRONFLEX FLOW TECHNOLOGY CO LTD**

EX26542

Zone A, European Industrial Park, No.389 Binhai Yi Road, Hangzhou Bay New Zone  
Ningbo, Zhejiang 315336 CHINA

Model	Rated Pressure, psig	Max Ambient Temp, °F	Nom Inlet by Outlet Size, in.	Assembly Length, ft (mm)	Max No. of 90° Bends	Min Bend Radius, in.	Equivalent Length of 1 in. Schedule 40 Steel Pipe (C = 120), ft	Flexibility Type
TU25-700 unbraided	175	225	1 by 1/2	2.3 (700)	1	4 (100)	30	Limited
TU25-1000 unbraided	175	225	1 by 1/2	3.3 (1000)	2	4 (100)	44	Limited
TU25-1200 unbraided	175	225	1 by 1/2	3.9 (1200)	3	4 (100)	54	Limited
TU25-1500 unbraided	175	225	1 by 1/2	4.9 (1500)	3	4 (100)	76	Limited
TU25-1800 unbraided	175	225	1 by 1/2	5.9 (1800)	3	4 (100)	86	Limited
TU25-700 unbraided	175	225	1 by 3/4	2.3 (700)	1	4 (100)	30	Limited
TU25-1000 unbraided	175	225	1 by 3/4	3.3 (1000)	2	4 (100)	49	Limited
TU25-1200 unbraided	175	225	1 by 3/4	3.9 (1200)	3	4 (100)	56	Limited
TU25-1500 unbraided	175	225	1 by 3/4	4.9 (1500)	3	4 (100)	77	Limited
TU25-1800 unbraided	175	225	1 by 3/4	5.9 (1800)	3	4 (100)	80	Limited

Unbraided flexible sprinkler hose with fittings, TU25 Series are intended to be installed with reducer (central) bracket and end bracket assembly in accordance with the manufacturer's installation instructions dated March 25, 2016.

# TRONFLEX

Trademark and/or Tradename:

Last Updated on 2016-04-07

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".